



# SWIVEL CASTOR WITH CENTRAL/DIRECTIONAL TOTAL BRAKE 200 MM, 120 KG

ART.-NR.: 390R 29K200R Z2351 CA

|                       |        |
|-----------------------|--------|
| <b>Diameter:</b>      | 200 mm |
| <b>Tread width:</b>   | 32 mm  |
| <b>Height:</b>        | 237 mm |
| <b>Offset:</b>        | 61 mm  |
| <b>Load capacity:</b> | 120 kg |



## Technical description

- sheet steel metal metal housing
- zinc passivated
- double ball bearing in swivel head
- up-to-date design with high-quality plastic cover
- protected from dust and water ingress by plastic sealing ring
- integrated selection mechanism with total lock “q”
- and directional locking “r”
- selection mechanism continually greased
- device to permit adjustment of the braking effect
- (without removing the castor or wheel)
- also available with other wheel variants

## Wheel

- thermoplastic elastomer tyre (TPE) iron grey RAL 7011 (Shore A 80)
- plastic wheel centre and thread guard silver grey RAL7001
- precision ball bearing
- >>Contact discoloration on unsealed grounds possible!<<

## Application area

- care beds
- hospital beds
- intensive care beds
- medical equipment
- op beds
- op tables